



**IMPORTANT NOTE:**

THIS LOADING CHART IS **NOT** TO BE USED IN FIELD FOR CONSTRUCTION OF BASKETBALL SUPPORT (LOCATIONS) THAT SHALL BE PLACED (BY OTHERS) WHEN APPLICABLE.

PLEASE CONTACT **AALCO MFG.** DIRECTLY FOR SUPPORT PLACEMENT INFORMATION.



1650 Avenue "H" St. Louis, MO 63125  
 ph. 314-544-4300 / 800-537-1259 / fx. 314-544-2386  
 c-mail: [engineering@aalcomfg.com](mailto:engineering@aalcomfg.com)

133WB		STATIC LOADS		DYNAMIC LOADS				
		A <sup>^</sup>	C,D <sup>^</sup>	FRONT IMP.		SIDE IMPACT		
BEAM HEIGHT				A <sup>^</sup>	C,D	A	C,D NORMAL	C,D SHEAR
16'		350	100	400	0	0	250	250
18'		370	100	400	0	0	250	250
20'		390	100	400	0	0	250	250
22'		410	100	400	0	0	250	250
24'		430	100	400	0	0	250	250
26'		450	100	400	0	0	250	250
28'		470	100	400	0	0	250	250
30'		490	100	400	0	0	250	250
32'		510	100	400	0	0	250	250
34'		530	100	400	0	0	250	250
36'		550	100	400	0	0	250	250
38'		570	100	400	0	0	250	250
40'		590	100	400	0	0	250	250